

Clean-n-Dry Premium Silicone Exterior Emulsion

The Product

Eureka Paints Clean-n-Dry is a Premium Silicone Exterior Emulsion having excellent Dirt Pick Up Resistance, water resistance, advanced anti algal properties. It has a very good sheen

Key Features

Eureka Paints Clean-n-Dry is a advanced durable all weather coating having very high dirt pick up resistance, very low water absorption apart from giving good algae resistance, colour fastness and very good sheen. Thus giving the building a fresh look for long period of time, which also reduces the maintenance cost

Substrate Suitability

Eureka Paints Clean-n-Dry can be applied on vast range of surfaces viz cement plaster, masonry, concrete, asbestos sheet ,POP, Gypsum etc.

How To Use











Surface Preparation

- Ensure that the substrate to be painted is free of any dirt, dust, oil, grease, any algal/fungal growth or any other type of contamination.
- This can be achieved by vigorous brushing of surface with media like wire, tar brush etc and cleaning with soft water.
- In case of pre painted surfaces - loose old paint etc should be thoroughly removed.
- Surfaces showing signs of chalking and flaking should be treated with some suitable sealer etc.

Touch Ups/Rectification

- Any touch up/ rectification required in the surface should be done with sand cement mortar only and it should be subjected to proper curing.
- For freshly plastered surface , care should be taken for proper curing and sufficient drying time.

Application System

Product	Application Tool	Thinner	Dilution	Touch Dry	Recoat*
Priming Eureka Paints Cement Paint	 Brush	Water	100%	1hr	2 Days After Minimum Curing - 3 Times
OR					
Eureka Paints EWP Exterior Waterbase Acrylic Primer	 Brush,  Roller,  Spray	Water	60-70%	30 mins	4 hrs
1st Coat Eureka Paints Clean n Dry Premium Silicone Exterior Emulsion	 Brush,  Roller,  Spray	Water	40-45%	1hr	4-6hrs
2nd Coat Eureka Paints Clean n Dry Premium Silicone Exterior Emulsion	 Brush,  Roller,  Spray	Water	40-45%	1hr	4-6hrs

* Recoat period is quoted for 25° C at 50% relative humidity - may vary under different conditions.

Technical Data

1)	Covering**	On normal masonry surface brush applied 1 Coat : 10.5 - 11.5 sq mtr / ltr at recommended DFT 2 Coats : 5.5 - 6 sq mtr / ltr at recommended DFT
2)	Recommended Dry Film Thickness(DFT)	60-70 microns for 2 coats
3)	Volume Solids	40 +/-2
4)	Weight Per Litre	1.32 +/-0.02
5)	Gloss/Sheen Levels	0 to 12 @ 60° head
6)	Viscosity	106KU +/- 2
7)	PH	8 to 9
8)	Water Absorption	Very Low
9)	Thinning	40-45% by volume with water
10)	Drying Time	Touch Dry 1hr Recoat 4-6 hrs
11)	Shelf Life	Minimum 1 yr when stored in original sealed container away from sunlight and excessive heat.
12)	Pot Life	24 hrs

**Actual coverage may vary on factors such as substrate porosity, method of application etc.

Precautions

Before Use

- Do not overdilute or over extend the brush
- Stir Well Before Use

Post Application

For performance optimisation - ensure proper washing and cleaning of structures at regular intervals.

Safety

Please refer to detailed MSDS of Clean n Dry for detailed information on safe handling of product.



Pack Sizes & Shade Range

Pack size availability:

1ltr, 4ltr, 10ltr, 20ltr

Available in Large Shade Range