

Pure Gold - Acrylic Distemper

The Product

Eureka Paints Pure Gold is a superior quality Acrylic Base Distemper which gives an emulsion like finish. It is a copolymer Acrylic coating that provides a smooth finish & better shade retention.

Key Features

- Eureka Paints Pure Gold Acrylic Distemper is a product which fulfill all parameters viz durability, beauty, cost effectiveness and value for money.
- Its special formulation makes it possible to develop clean shades and enables very long shade retention.
- It provides a smooth and beautiful look to the surface.

Substrate Suitability

Eureka Paints Pure Gold is compatible to the following substrates - POP, Gypsum, Gypsum board false ceilings, asbestos sheets, concrete, plaster etc.

How To Use

Surface Preparation

 Apply 2 coats of Eureka Paints Pure Gold Acrylic Distemper for repainting and 3 coats for fresh surface painting as given below:

Application System

,					
Product	Application Tool	Thinner	Dilution % (by vol)	Application Viscosity (sec)	Recoat* Period (hrs)
Sand the surface with Emery paper 180 and wipe clean with cloth			(5) (6)	1100011 , (000)	Tonou (III)
Eureka Paints IWP Interior waterbase Acrylic Primer (Optional)	Sprush ♠C** Spray	Water Water	60-70% 70-75%	30-40 20-25	3-4hrs 3-4hrs
Eureka Paints Poly Plast Acrylic Putty	Putty Knife	Water	As required	N.A.	4-6hrs
Sand down with Emery Paper 180 and wipe clean					
Eureka Paints IWP Interior waterbase acrylic Primer	ॐ Brush Æ* Spray	Water Water	60-70% 70-75%	30-40 20-25	3-4hrs 3-4hrs
Sand down with Emery paper 320 and wipe clean					
1st Coat Eureka Paints Pure Gold Acrylic Distemper	➢ Brush Æ* Spray	Water Water	60%-70% 70%-75%	20-30 20-25	3-4hrs 3-4hrs
2nd Coat Eureka Paints Pure Gold Acrylic Distemper	➢ Brush ♠ Spray	Water Water	60%-70% 70%-75%	20-30 20-25	3-4hrs 3-4hrs

^{*} Recoat period is quoted for 25° C at 50% relative humidity - may vary under different conditions.



Technical Data

1) **Covering**** On smooth primed masonry surface by brushing:

1 coat : 16-18 sq mtr/ltr 2 coats : 07-10 sq mtr/ltr

2) **Drying time:** Surface Dry time \sim 10-15 minutes

3) **Volume Solids** 36+/-2

4) Weight per ltr 1.40 + /-0.02

5) **Gloss/Sheen Levels** 0-4 on glass plate at 60°-Matt finish with slight sheen

6) **PH** 8 to 9

7) **Touch Dry** 20 mins

8) **Shelf Life** Minimum 1 year from date of manufacture in original tightly closed containers

9) **Pot Life** Use within 24 hrs

** Actual coverage may vary on factors such as substrate porosity, method of application etc. It is advisable and strongly recommended to check the covering on respective surface before use.

Precautions

Before Use

- Do not over dilute or over extend the brush
- Stir Well Before Use

Post Application

for removing stain, sponge clean with a mild soap solution and wipe clean. Ensure a drying time of 1 week before cleaning.

No rigorous scrubbing.

Safety

Please refer to detailed MSDS of Pure Gold Distemper for detailed information on safe handling of product.



Pack Sizes & Shade Range

Pack size availability:

1kg, 2kg, 5kg, 10kg, 20kg

Available in Large Shade Range



Regd. Off.: 5 Meghdoot, 2nd Floor, Plot No. 283, Flank Road, Opp. S R Mehta (Kikabhai) Hospital, Sion (E), Mumbai - 400022.

Manufactured at: Eureka Paints, Unit No.A 743,TTC Industrial Area, MIDC Village Khairne , Near Ruchit Palace Hotel, Navi Mumbai.

Customer Care:

Phone: +91-22-24096182 / 24070437 | Mobile: +91-9867466661 Email: info@eurekapaints.in | Web: www.eurekapaints.in