

## Silver Distemper

### The Product

- Eureka Paints Silver Distemper is a Co-polymer water-based, interior wall finish.
- It is an economical product which provides good finish at low cost.

### Key Features

- Variety of shades, longer shade retention and smooth and matt finish.

### Substrate Suitability









Eureka Paints Silver Distemper is compatible to the following substrates - POP, Gypsum, Gypsum board false ceilings, asbestos sheets, concrete, plaster etc.

### How To Use

#### Surface Preparation

Apply topcoats of Eureka Paints Silver Distemper as follows:

### Application System

Product	Application Tool	Thinner	Dilution % (by vol)	Application Viscosity (sec)	Recoat* Period (hrs)
Sand the surface with Emery paper 180 and wipe clean with cloth					
<b>Eureka Paints IWP</b> Interior waterbase Acrylic Primer (Optional)	 Brush  Spray	Water Water	60-70% 70-75%	30-40 20-25	3-4hrs 3-4hrs
<b>Eureka Paints Poly Plast</b> Acrylic Putty	 Putty Knife  Spray	Water	As required	N.A.	4-6hrs
Sand down with Emery Paper 180 and wipe clean					
<b>Eureka Paints IWP</b> Interior waterbase acrylic Primer	 Brush  Spray	Water Water	60-70% 70-75%	30-40 20-25	3-4hrs 3-4hrs
Sand down with Emery paper 320 and wipe clean					
1st Coat <b>Eureka Paints Silver Distemper</b>	 Brush	Water	65-75%	20-25	3-4hrs
2nd Coat <b>Eureka Paints Silver Distemper</b>	 Brush	Water	65-75%	20-25	3-4hrs

\* Recoat period is quoted for 25°C and 50% Relative humidity, these may vary under different conditions.

# Silver Distemper

## Technical Data

- |    |                           |  |
|----|---------------------------|--|
| 1) | <b>Covering**</b>         | The coverage on smooth primed masonry surface with the recommended application procedure is:<br>Re-painting (2 coats):10-12 sq mts/kg<br>New surface (3 coats):7-8 sq mts/kg |
| 2) | <b>Gloss/Sheen Levels</b> | Matt   |
| 3) | <b>PH</b>                 | 8 to 9   |
| 4) | <b>Drying Time</b>        | Dry to touch 30 minutes  |
| 5) | <b>Shelf Life</b>         | Minimum 1 year in original tightly closed containers away from direct sunlight and excessive heat  |
| 6) | <b>Pot Life</b>           | Use within 24 hrs  |

\*\* Actual coverage may vary on factors such as substrate porosity, method of application etc.  
It is advisable and strongly recommended to check the covering on respective surface before use.

### Precautions

#### Before Use

- Do not over dilute or over extend the brush
- Stir Well Before Use

### Safety

Please refer to detailed MSDS of Silver Distemper for detailed information on safe handling of product.



### Pack Sizes & Shade Range

#### Pack size availability:

**1Kg, 2Kg, 5Kg, 10Kg, 20Kg**

**Available in large shade range**

#### Customer Care :